HARD COAT CLEANING TINTING PERIPHERALS CONSUMABLES EXPERTISE





TINTING AT ITS BEST

■ PRODUCTION CAPACITY

• Lenses / rack 10

• Type of lenses: all types \varnothing 40 to 80mm

• Tinting tank capacity .. : 5 liters















HARD COAT CLEANING TINTING PERIPHERALS CONSUMABLES **EXPERTISE**



SPECIFICATIONS

- Up to 10 tinting tanks according to needs
- From 2 to 10 digital gradient systems
- Stirring by rotating magnet
- Electropolished stainless steel tinting tanks
- Accurate temperature control +/- 1°C
- Tank removable easily
- Flexible drain with 3 ways valve (can or sewage) → Adaptable system
- Modular extraction of the tinting vapours
- Possibility to custom the size and position of the gradient
- User friendly HMI

BENEFITS

- → A modular system according to needs
- → Easy to clean
- → For stable results
- → For an easy maintenance
- → Safe working station
- → Make any gradient wished
- → Gradient profile easy to be defined
- → Create the recipes
- → Follow in live the cycle

TECHNICAL DATA

Machine in 1 part

Dimensions 250 cm x 92 cm x 215 cm

Weight ~ 500 kg Electricity 12 kW / 400 V

Compressed air No

CE and UL compliance



PERIPHERALS

- Water softener (raw water supply)
- Draining tank with lift pump
- Ergonomic preparation/control station
- Lens-holders and rack for 10 lenses



